

SECTION 28, T. 11 S., R 43 E., W.M.

PARTITION PLAT NO.

P2007-~~019~~^{K.P.} 020

BASIS OF BEARING

N. 88° 34' 50" W., 2653.56'
[N. 88° 34' 50" W., 2653.52']

N. 88° 34' 50" W., 1326.78' N. 88° 34' 50" W., 1326.78'

N. 00° 12' 17" W., 2842.88'
N. 00° 12' 54" W., 2842.98'
N. 00° 12' 54" W., 1421.49'

N. 89° 13' 07" W., 1330.95' N. 89° 13' 07" W., 1330.95'

N. 00° 12' 17" W., 5538.77'
{N. 00° 12' 17" W., 5538.57'}
[N. 00° 12' 30" W., 5538.8']

N. 00° 12' 54" W., 2695.69'
N. 00° 12' 17" W., 2695.79'

N. 89° 51' 09" W., 1335.28' N. 89° 51' 09" W., 1335.28'

N. 89° 51' 09" W., 2670.56'

N. 00° 35' 09" W., 2716.13'

N. 00° 35' 09" W., 2716.13'

N. 89° 25' 21" W., 2688.34'

N. 89° 26' 44" W., 2703.29'

N. 01° 41' 55" W., 2736.53'

N. 00° 12' 17" W., 2695.69'

N. 00° 12' 54" W., 2695.79'

N. 00° 12' 17" W., 5538.77'
{N. 00° 12' 17" W., 5538.57'}
[N. 00° 12' 30" W., 5538.8']

N. 00° 12' 54" W., 1421.49'

N. 00° 12' 17" W., 2842.88'
N. 00° 12' 54" W., 2842.98'

N. 00° 12' 54" W., 1421.49'

N. 00° 12' 17" W., 5538.77'
{N. 00° 12' 17" W., 5538.57'}
[N. 00° 12' 30" W., 5538.8']

N. 00° 12' 54" W., 1421.49'

N. 00° 12' 17" W., 2842.88'
N. 00° 12' 54" W., 2842.98'

N. 00° 12' 54" W., 1421.49'

FOUND 2.5" BRASS CAP MONUMENT FOR NORTH 1/4 CORNER OF SECTION 28 SET BY BAKER COUNTY SURVEYOR, 1995

FOUND 2.5" BRASS CAP MONUMENT FOR EAST 1/4 CORNER OF SECTION 28 SET BY BAKER COUNTY SURVEYOR, 1995

FOUND NAIL IN RAILROAD TIE AT INTERSECTING FENCES. POSITION HELD FOR SOUTHEAST CORNER OF SECTION 28

CALCULATED WEST 1/4 CORNER OF SECTION 28 FROM BAKER COUNTY SURVEY NO. 11-43-6

FOUND 2.5" BRASS CAP MONUMENT FOR SOUTHWEST CORNER OF SECTION 28 SET BY BAKER COUNTY SURVEYOR, 1994

FOUND 2.5" BRASS CAP REFERENCE MONUMENT FOR NORTHEAST CORNER SECTION 28 BEARS S. 0° 12' 54" E., 1.00' FROM ACTUAL CORNER POSITION SET BY BAKER COUNTY SURVEYOR, 1994

LEGEND

- ◇ Set 12" bridge spike at intersection of existing East-West fence and old fence remnants to the North
- Found, monument as noted.
- Found, brass cap monument as noted.
- { } Record Data Per Ba. Co. Surv. No. 11-43-6.
- [] Record Data Per Ba. Co. Surv. No. 11-43-7.

BASIS OF BEARING

BAKER COUNTY SURVEY NO. 11-43-7, NORTH LINE OF THE NORTHWEST 1/4 OF SECTION 28 BEARS S. 88° 34' 50" E.



1" = 500'

REGISTERED PROFESSIONAL LAND SURVEYOR

THOMAS J. HANLEY
JULY 13, 1979
1817

Renews June 30, 2009

HANLEY ENGINEERING, INC.

2043 MAIN STREET
P.O. BOX 701

BAKER CITY, OREGON 97814
(541) 523-3803

REFERENCES

- Baker County Survey No. 11-43-6
- Baker County Survey No. 11-43-7