DEED REFERENCES

Book 53, page 404

Status of Record Title No.

438056AM, dated January 22.

2021, prepared by Amerititle

B19 19 0068

Sheet 1 of 2

REPLAT NUMBER 72021-004

A replat of Lots 3 and 4, Block 5, J.M. Boyd's Addition to the City of Baker City Situated in the Northeast quarter of the Southeast quarter of Section 17, Township 9 South, Range 40 East of the Willamette Meridian, Baker County, Oregon

40

(3)

S T R E E T

C A M P B E L L-296.50--108.25-296.06 (VARIABLE WIDTH, SEE NARRATIVE) S89°55'24"E POINT OF BEGINNING -108.25-**108.03** 108.03 40.00 40.00 40 PARCEL 1 5,743 sq. ft. ES89°55'24"E \mathcal{E} PARCEL 2 \mathcal{F} 5,062 sq. ft. 100.07 S S89°55'24"E 108.07 falls South N89°55'24"W 108.07 0.7 ft. and (12) East 1 ft. \mathcal{S} 40 40

-108.25-108.11

PMADISONS89°55'23"E

-108.25-

108.11

S89*55'23"E

S T R E E T[296.29] -296.50-296.25

216.22

NARRATIVE

D

Z

E

 ∞

S0.37'53"W

(11)

This partition was done at the request of Haden Damschen, on behaf of Damschen LLC. Mr. Damschen wanted to replat the lots as shown. To establish block exteriors, I recover monuments within J.M. Boyd's Addition as shown. The original plat of J.M. Boyd's Addition shows the North line being located along the center of section, which is consistent with the plats of Father Deroo's and Brattain and McComas Addition. Though the width of Campbell Street had been shown on various maps to have an 80 foot width (Survey 09-40-0785 and 09-40-0297), the width is not specified on the original plat. I find that the centerline monuments within J.M. Boyd's addition would have a 5-7 foot excess in distance to the Section line, if an 80 foot width of Campbell Street were assumed. If an 80 foot width from the center of section line were used, and a standard proportion were done along the North tier of blocks in J.M. Boyd's Addition, this would be deleterious to lines of possession. I therefore hold the bearing of the line between the monuments at 2nd and Madison and 2nd and Broadway, and extend this North a record 240 feet. Along First Street, I hold the monuments at the intersections of Madision and 1st and the one at Baker and 1st, and extend this North record platted 240 feet. I drive a line between these to establish the North line of the Block. Interior lot lines are established by standard proportion. Along the West side of the property, I set monuments at the East edge of the alley. I find no other unusual conditions with this partition.

REGISTERED PROFESSIONAL LAND SURVEYOR OREGON JUNE 2, 2010

83571 Renewal Date: June 30, 2021

JEFFREY S. HSU

Found 1" iron pipe in monument box

Found 3/4" iron pin (unless otherwise specified) in monument box

Position of intersecting punch marks on manhole rim

Set $5/8" \times 30"$ iron pin with plastic cap marked BGB SURVEY MARKER

Centerline

Fenceline

Easement Line

Record measurement as per Survey Number 9-40-0110BC

Record measurement as per Survey Number 9-40-0011BC

Record measurement as per Survey Number 9-40-0189

Record measurement as per plat of J.M. Boyd's Addition

BASIS OF BEARING

True geodetic North at the corner common to Sections 8. 9, 16 and 17, Township 9 South, Range 40 East of the Willamette Meridian, as determined by GPS observation

SCALE: 1"=40'

REFERENCE MATERIAL

Survey Number AD 17-23 Survey Number AD 19-17 Survey Number AD 20-13

Survey Number 09-40-0011BC Survey Number 09-40-0110BC

Survey Number 09-40-0272 Survey Number 09-40-0293 Survey Number 09-40-0297

Survey Number 09-40-0785 Plat of J.M. Boyd's Addition

Plat of Father Deroo's Addition

Plat of Brattain and McComas Addition

NOTES AND EASEMENTS

Easement for alley, 8 ft. wide, including terms and provisions thereof, reserved by deed recorded January 28. 1903 in Book 53, Page 404, deed records of Baker County

