

T. 6 S., R. 45 E., Willamette Meridian, Oregon

FBET

Latitude: 45° 03' 05.861" N. Longitude: 117° 11' 00.875" W.

Geographic positions were also determined for other PLSS corners in the course of this survey. The geographic positions are reported with the corner description.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 S., R. 45 E., Willamette Meridian, Oregon**

(Restoring the survey by William B. Barr in 1884)

Beginning at the cor. of secs. 15, 16, 21, and 22, monumented with an iron spike, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, from which the original bearing trees

A fir, 16 ins. diam., bears S. 9° E., 24.8 ft. dist., with fragmentary scribe marks visible on partially healed double blaze.


A fir, 14 ins. diam., bears S. 50½° W., 44.2 ft. dist., with fragmentary scribe marks visible on partially healed double blaze.

A fir, 18 ins. diam., bears N. 14½° W., 18.5 ft. dist., with fragmentary scribe marks visible on partially healed double blaze.

Corner is located on very steep, rocky W. slope, approximately 30 ft. W. of the top of ridge.

From this point, the witness cor. established by Griffith, in 1982, and reported by Griffin, bears N. 88° 28' 00" E., 58.41 ft. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

BAGETT GRIFFITH & ASSOC
WC



from which the remaining bearing trees mkd. by Griffith