

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 45 E., Willamette Meridian, Oregon

FEET	
	<p>A fir, 14 ins. diam., bears N. 2½° E., 48.8 ft. dist., with scribe marks X BT visible on partially opened double blaze.</p> <p>A fir, 16 ins. diam., bears S. 55° E., 11.2 ft. dist., with scribe marks X BT visible on partially opened double blaze.</p> <p>A fir, 24 ins. diam., bears S. 30° E., 24.4 ft. dist., with scribe marks X BT visible on partially opened double blaze.</p>
	<p>N. 2° 47' 10" W., bet. secs. 15 and 16.</p>
	<p>Along ridge, bears N. and S., through scattered timber.</p>
2596.83	<p>Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance, there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 6 S R 45 E 1/4 S 16   S 15</p> <p style="text-align: center;">2004</p>
	<p>from which</p>
	<p>A subalpine fir, 14 ins. diam., bears N. 13¼° E., 24.2 ft. dist., mkd. 1/4 S15 BT.</p>
	<p>A subalpine fir, 16 ins. diam., bears S. 86¼° W., 32.1 ft. dist., mkd. 1/4 S16 BT.</p>
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located on moderate N. slope in dense timber and undergrowth.</p>
5193.66	<p>Point for the cor. of secs. 9, 10, 15, and 16, at proportionate position using 3 point control, N., S., and E., there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>