

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 45 E., Willamette Meridian, Oregon

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 6 S R 45 E S 10 AP 1661 S 15 2004</p> </div> <p>from which</p> <p>The marks BXO, on a basalt boulder, 2 x 2 x 3 ft. high, bear N. 58¾° E., 13.9 ft. dist.</p> <p>A Douglas fir, 23 ins. diam., bears S. 13 ¾° W., 44.5 ft. dist., mkd. X at breast height, and BT at the base.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located on the highest point of a ridge, bears N. 55° W. and S. 55° E.</p> <p>The geographic position (NAD 1983 (98)) of this corner is: Latitude: 45° 03' 05.771" N. Longitude: 117° 11' 48.159" W.</p> <p>Descend steep W. slope, through sparse timber.</p>
4700	Trail, 2 ft. wide, bears N. 20° W. and S. 20° E.
5301.00	The cor. of secs. 9, 10, 15, and 16.
	<hr/> <p>N. 1° 49' 29" E., bet. secs. 9 and 10.</p> <p>Along steep W. slope, through scattered timber.</p>
2595.01	<p>Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 6 S R 45 E 1/4 S 9   S 10 2004</p> </div>