Dependent Resurvey of a Portion of the Subdivisional Lines, T. 6 S., R. 45 E., Willamette Meridian, Oregon

FEET

from which

The marks BXO, on basalt outcropping, $4 \times 3 \times 2$ ft. high, bear S. 70° E., 68.0 ft. dist.

The marks BXO, on a basalt boulder, $2\frac{1}{2} \times 1\frac{1}{2} \times 1$ ft. high, bear N. 15% W., 29.4 ft. dist.

Deposit a magnet in a white plastic case at the base of the stainless steel.post.

Corner is located on steep W. slope.

Ascend along steep W. slope, through scattered timber.

5190.02

The cor. of secs. 3, 4, 9, and 10, monumented with the original granite stone, $24 \times 7 \times 7$ ins. (record: $20 \times 7 \times 6$ ins.), firmly set, projecting 6 ins. above the ground, with 4 grooves visible on the S. face, and 2 grooves visible on the W. face, from which the original bearing trees

- A whitebark pine with 6 stems, to center stem, 14 ins. diam., bears S. 69½° E., 80.5 ft. dist., with a healed blaze. (Record: spruce, S. 66½° E.)
- A whitebark pine, 15 ins. diam., bears S. 48° W., 112.2 ft. dist., with scribe marks R45E S9 B visible on partially opened blaze. (Record: spruce)

At the corner point

Set a stainless steel post, 28 ins. long, 2% ins. diam., 25 ins. in the ground, in a collar of stone, with brass cap mkd.

2004

from which a new bearing object

The marks BXO, on the S. face of a boulder, $5 \times 2 \times 2$ ft. high, bear N. 69% W., 45.5 ft. dist.

Incorporate the original stone in the collar of stone and deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located on a ridge, bears N. and S.