


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

H-2

History of original corner establishment:

None previously established.



Description of corner evidence found:

None

Description of monument and accessories established to perpetuate the original location of this corner:

At the corner point set a 2 1/2" x 30" alum. pipe with a 2 1/2" alum. cap 24" into the ground. Constructed a 36" dia. stone mound around the monument. The cap is marked as shown in the corner diagram.

From the corner point:

Two Witness corners were set to perpetuate the corner. A description of the two WC corners accompany this filing as 2 of 3 and 3 of 3.

*Witness corners were needed because the true corner point lands in the bottom of Balm Creek Reservoir.


This corner was monumented to USFS specifications on August 3, 1987, witnessed by Tom Fisk, Larry McBroom and Andy Marlette.

Office of... County Surveyor... County of... Baker
State of... OR... I hereby certify that the within instrument was filed in this office for record on the... day of... 19...

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)



James D. Harley
OREGON
SEPTEMBER 21 1987
JAMES D. HARLEY
1206

☆ GPO—798-276

FILED 10/18/88
BAKER COUNTY SURVEYOR
SURVEY NO. 7-43-154