

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

(10)

History of original corner establishment:

No previous history.

DIAGRAM
Cap Stamped
T 7 S
E 1/16
S 21
S 28
R 45 E
1978
ORLS 645

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2 1/2" x 30" galv. iron pipe w/brass cap stamped as shown above in the ground in mound of stone.

New bearing trees:

12" fir bears N 80 E, 24.90 ft. scribed 1/16S S21 BT.  
6" fir bears S 55 E, 32.70 ft. scribed 1/16S S28 BT.

I hereby certify the above corner monument was re-established as herein described in August 1978.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*James H. Hambleton*  
8-21-78

OREGON  
JULY 10, 1964  
JAMES H. HAMBLETON  
645

Witnesses:

*Leonard E. Shuman*  
Crew Chief  
*L. D. Shubert*  
Instrument Man

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO—798-276

FILED 9-26-78

BAKER COUNTY SURVEYOR

SURVEY NO. 7-45-29