

(16)

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

No previous history.

DIAGRAM  
Cap Stamped  
T 7 S  
SE-C-1/16  
S 28  
R 45 E  
1978  
ORLS 645

Description of corner evidence found:

None

Description of monument and accessories established to perpetuate the original location of this corner:

I set a 2 1/2" x 30" galv. iron pipe w/brass cap stamped as shown above in the ground in mound of stone.

New bearing trees:

10" fir bears S 79 W, 33.28 ft. scribed 1/16 S 28 BT.  
12" pine bears S 08 W, 64.90 ft. scribed 1/16 S 28 BT.

I hereby certify the above corner monument was re-established as herein described in August 1978.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*James H. Hambleton*  
8-21-78

OREGON  
JULY 10, 1964  
JAMES H. HAMBLETON  
645

Witnesses:

*Leonard C. Green*  
Crew Chief  
*L. D. Haly*  
Instrument Man

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO—798-276

FILED 9-26-78  
BAKER COUNTY SURVEYOR  
SURVEY NO. 7-45-35