

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

21

History of original corner establishment:

No previous history

<b>DIAGRAM</b>
Cap Stamped
T 7 S
N-C-1/16
S 30
R 45 E
1978
ORLS 645

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2 1/2" x 30" galv. iron pipe w/brass cap stamped as shown above, in the ground and placed a large mound of stone and dirt around the monument.

New bearing trees:

6" pine bears S 56 W, 66.00 ft. scribed 1/16S S30 BT.  
15" pine bears S 84 E, 17.25 ft. scribed 1/16S S30 BT.

I hereby certify the above corner monument was re-established as herein described in August 1978.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*James H. Hambleton*  
8-21-78

OREGON  
JULY 10, 1961  
JAMES H. HAMBLETON  
645

Witnesses: Leonard E. Spence  
Crew Chief

L. D. Shady  
Instrument Man

Office of.....County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19....

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO—798-276

FILED 9-26-78  
BAKER COUNTY SURVEYOR  
SURVEY NO. 2-45-40