


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

No previous history



Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2 1/2" x 30" galv. iron pipe w/brass cap stamped as shown above, in the ground and placed a large mound of stone and dirt around the monument.

New bearing trees:

12" pine bears N 36 W, 18.50 ft. scribed C 1/4 S 30 BT.
10" pine bears S 50 W, 47.25 ft. scribed C 1/4 S 30 BT.

I hereby certify the above corner monument was re-established as herein described in August 1978.

REGISTERED PROFESSIONAL LAND SURVEYOR

James H. Hambleton
8-21-78

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

Witnesses:

Leonard E. Green
Crew Chief

L. D. Shulby
Instrument Man

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO—798-276

FILED 9-26-78

BAKER COUNTY SURVEYOR

SURVEY NO. 7-45-42