


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: *NONE*



Description of corner evidence found: *NONE*

Description of monument and accessories I established to perpetuate the original location of this corner:

*AT CALCULATED POSITION I SET A 2" x 30" GALV. IRON PIPE W/ BRASS CAP STAMPED AS SHOWN ABOVE, FROM WHICH:
NEW BT, 14" PINE, SCRIBED "C $\frac{1}{4}$ S 33 BT" BEARS N 9° E 123.0 FT.
NEW BT, 18" PINE, SCRIBED "C $\frac{1}{4}$ S 33 BT" BEARS N 63 $\frac{1}{2}$ ° W, 205.9 FT.*

I SET THE 2" PINE 16" IN GROUND AND BUILT A LARGE MOUND OF STONE AROUND IT.

I SET A STEEL POST 3' E. OF COR. W/ SIGN 54-9

I PRINTED A RED BAND AROUND BOTH BT'S, AND TAGGED THEM W/ SIGN 54-3

I HEREBY CERTIFY THE ABOVE CORNER MONUMENT WAS ESTABLISHED AS HEREIN DESCRIBED ON JUNE 14, 1980.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Victor M. McLind

OREGON
JULY 17, 1970
VICTOR M. McLIND
934

WITNESS: *Doug McFerd*

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)