

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

0-23

History of original corner establishment:
No previous history.

DIAGRAM
Cap Stamped
T 7 S
C-N-1/16
S 24
R 45 E
1981
ORLS 645

Description of corner evidence found:
None

Description of monument and accessories I established to perpetuate the original location of this corner:

At the 1/16 corner location I set a 2½" brass cap on a 30" galv. iron pipe, 4" above surface of ground, from which I set two bearing trees.

A Pine 6" dia. bears N 3100 W, 25.0' horiz. dist. and scribed 1/16 S S 24 BT.

A Doug. Fir 8" dia. bears S 51 15 W, 27.0' horiz. dist. and scribed 1/16 S S 24 BT.

I hereby certify the above corner monument was established as herein described during May 1981,

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

Witnesses:

Mike Cain
Mike Cain (Inst. Man)

Mark Cain
Mark Cain (Chainman)

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL) (DEPUTY)