


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

P-23

History of original corner establishment:

No previous history.



Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

At the  $\frac{1}{4}$  corner location I set a  $2\frac{1}{2}$ " brass cap on a 30" galv. iron pipe 2" above the surface of the ground, from which I set two bearing trees:

A Pine 12" dia. bears N 66 45 W, 64.55' horiz. dist. and scribed C  $\frac{1}{4}$  BT.

A Pine 8" dia. bears S 80 00 W, 88.12' horiz. dist. and scribed C  $\frac{1}{4}$  BT.

I hereby certify the above corner monument was established as herein described during June 1981.

Witnesses: Mike Cain  
 Mike Cain, Inst. Man  
Mark R Cain  
 Mark Cain, Chainman

REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR

*James H. Hambleton*

OREGON  
 JULY 10, 1964  
 JAMES H. HAMBLETON  
 645

Office of..... County of.....  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of....., 19.....

..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)