CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by W.B. Barr under GLO Contract No. 443 dated May 29, 1882.

Surveyor General's records state:

Set basalt rock 13 X 9 X 7 ins 11 ins in the ground for 1/4 Sec corner marked 1/4 on the North side and raised mound of rock along side; pits impracticable.

DIAGRAM

T 7 S R 46 E

1/4 S 24 / S 25

Description of corner evidence found:

A basalt stone 13x9x6 ins firmly set and marked 1/4 on the North face and a mound of stone 3 ft North.

(A fence corner bears N 08° 30' E, 77.7 ft dist from which the fence runs East, West, and South)

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2½ inch brass cap on a 2 inch iron pipe 31 ins long 16 ins in the ground to solid rock with a surrounding rock mound and a 6 ft steel fence post 3 ft East with signs 54-4 and 54-2 attached. Buried original stone alongside brass cap.

Brass cap marked thus: T 7 S R 46 E

1/4 S 24 / S 26

1979

ORLS 1639

Bearing objects:

A 1 inch iron pipe 28 ins long bears S 23° E, 15.6 ft dist
A 1 inch solid steel rod 40 ins long bears N 32° E, 14.5 ft dist

REGISTERED PROFESSIONAL LAND SURVEYOR

William L Hanley

OREGON
JULY 14, 1978
WILLIAM L. HANLEY
1639

I hereby certify that the above monument was properly re-established as herein described on July 31, 1979 witnessed by Tracy Labaree and Jim DeMastus.

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of..... , 19.....

..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

FILED Aug. 1, 1979
BAKER COUNTY SURVEYOR
SURVEY NO. 7-46-25

☆ GPO 799-509