



Meridian based on Solar Observation

U.S. GOVERNMENT LANDS
 SECTION 15
 NE 1/4 (011)
 NE 1/4 SE 1/4, SE 1/4 SE 1/4, SW 1/4 SE 1/4, SE 1/4 SW 1/4
 SECTION 22
 NE 1/4 (011)
 W 1/2 SE 1/4, SW 1/4 (011), NW 1/4 (011)

- LEGEND**
- Set 2 1/2" brass cap on 2" x 31" iron pipe at proportionate distance.
 - ⊙ Found original GLO corner - Set 2 1/2" brass cap on 2" x 31" iron pipe.
 - Found monument of record.
 - ⊙ Record GLO line tree.
 - () GLO record bearing and distance.
 - Property boundary posted.
 - [] Record of Survey No. 7-46-1 Filed July 12, 1974.

REGISTERED PROFESSIONAL LAND SURVEYOR
 William L. Hanley
 OREGON
 JULY 14, 1978
 WILLIAM L. HANLEY
 1639

RECORD OF SURVEY PLAT

SCATTER-DRY CADASTRAL SURVEY

U.S. FOREST SERVICE CONTRACT NO. 53-04HI-9-7414N

Surveyed July 9 to Sept. 30, 1979

Scale 1" = 500'

FILED Nov 23, 1979
 BAKER COUNTY SURVEYOR
 SURVEY NO. 7-46-74

SURVEYED BY HANLEY ENGINEERING

NOTE: FOR MONUMENTATION RECORDS SEE CERTIFIED RECORD OF CORNER MONUMENTATION SHEETS FILED SEPARATELY.