

R 46 E

19  
3019 20  
30 29

SEC. 30 T. 7 S., R. 46 E., W. M.

BASIS OF BEARING:  
SUR. NO. 7-46-79A

N. 01° 15' 25" E.

2721.00'

N. 87° 41' 15" E.

1356.65'

678.32'

678.33'

N. 02° 18' 50" E.

1402.22'

1402.22'

N. 88° 45' 27" E.

664.70'

N. 02° 49' 42" E.  
(to sec. line)

1415.76'

1429.41'

N. 03° 19' 55" E. 2,858.81'

1429.40'

N. 89° 52' 20" E.

1302.62'

651.31'

651.31'

30 29

Set monument on N line county  
road N 02° 49' 42" E. 30.0 feet  
from the SW corner of the E<sub>2</sub>  
of the SE<sub>4</sub> SE<sub>4</sub> of Sec 30.

## LEGEND

- Found, monument of record
- Set  $\frac{5}{8}$ " x 30" rebar with plastic cap marked "HANLEY ENGINEERING PLS 1206".

## NARRATIVE

This survey to mark on the ground the monument shown and described herein for Roy Hearne was based on Survey No. 7-46-79A. Monumentation resulting from that survey was recovered and verified, prior to establishing the two monuments established this survey.

## MAP OF SURVEY

THE CENTER OF THE E<sub>2</sub> OF THE SE<sub>4</sub> OF  
SECTION 30, T 7 S., R 46 E., W.M.

Surveyed for Roy Hearne

April 10, 1987

Scale 1" = 800'

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

James D. Hanley

OREGON  
SEPTEMBER 23, 1977  
JAMES D. HANLEY  
1206

FILED 7-24-87

BAKER COUNTY SURVEYOR

SURVEY NO. 7-46-149