

True Meridian determined by Solar Observation

Found 1" bolt used as 1/4 cor. com. to Sec's 25 & 30 TBS R39E WM.

Found 1 1/4" iron pin in Reno's corner used as section corner.

(East GLO)
(78.50 ch)
Found mound of stone as per GLO notes, for the 1/4 cor. bet. 19 & 30, TBS, R39E WM

Set 3/4" iron pipe in fence line for true w-c 1/4 cor.

Set 5/8" iron pin in fence line for corner 30 feet of road center line.

1/4 cor. has not been relocated on the ground.

County road @ bears S89°53'30"W, Hanley used an assumed bearing of west in the survey of the road.

County road @ bears S89°50'00"W, Hanley used an assumed bearing of west for road survey.

SURVEY OF SECTION 30, TBS, R39E, WM
Scale 1" = 400'

Date 7-14-70

LEGEND:

- Corner found in place.
- Corner set this survey
- Point with no pin set.

Sta 0+00 is located 10.70 feet south of 1/4 corner.

REGISTERED
OREGON
LAND SURVEYOR
James H. Hambleton
JULY 10, 1964
JAMES H. HAMBLETON
645

FILED July 16, 1970
BAKER COUNTY SURVEYOR
SURVEY NO. 8-39-3

Rec'd 1:30 PM
July 16, 1970 J. Hambleton

