


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by W. B. Barr under contract dated September 10, 1880.

Surveyor's General record states:

Marked volcanic rock 12 ins. x 10 ins. x 6 ins. and dug pits.




Description of corner evidence found:

Found 12 ins. x 8 ins. x 6 ins. lava rock in a fence line. Fence bears North and South.

Description of monument and accessories established to perpetuate the original location of this corner

Set a 2½ inch brass cap on a 1 inch iron pipe, 30 inches long, 24 inches in the ground, and buried stone 5 ft. North.

Monument marked thus:



Corner remonumented April 18, 1978.

Office of County Surveyor County of Baker  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the 3 day of May, 1978.  
 \_\_\_\_\_ by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

FILED May 3, 1978  
 BAKER COUNTY SURVEYOR  
 SURVEY NO. 8-43-6

REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR  
*James D. Hanley*  
 OREGON  
 SEPTEMBER 23, 1977  
 JAMES D. HANLEY  
 1206