

INDEX No. V-13

History of original corner establishment:

Corner was originally established in 1881 by Herman D. Gradon, under General Land Office Contract Number 416. Surveyor General's Notes state:
Set a post 4 ft. long, 4 ins. square 24 ins. in the ground for cor. to secs. 27, 28, 33 & 34, marked

DIAGRAM

T9S R37E
S28|S27
S33|S34
1971
(BLM CAP)

T9S S27 on NE
R37E S34 on SE
S33 on SW and
S28 on NW face, with 1 notch on S and 3 notches on E edges

from which:

- A pine 18 ins. diam. bears N50°E, 10 lks. dist. marked T9S R37E S27 BT
- A pine 12 ins. diam. bears S10°E, 64 lks. dist. marked T9S R37E S34 BT
- A fir 15 ins. diam. bears S15°W, 67 lks. dist. marked T9S R37E S33 BT
- A pine 20 ins. diam. bears N20°W, 21 lks. dist. marked T9S R37E S28 BT

In 1971 Owen C. Chatters II, Cadastral Surveyor for the BLM remonumented this corner under Special Instructions dated May 3, 1957, Group 350. BLM records states: The cor. of secs. 27, 28, 33 and 34, determined at record bearing and distance from the remains of the original bearing trees: A pine stump, 20 ins. diam., bears N50°E, 10 lks. dist., with scribe marks BT visible on open blaze. A root hole, bears S10°E, 64 lks. dist., with a down pine alongside, 14 ins. diam., with scribe marks T9S R37E S34 BT visible on open blaze. A fir, 18 ins. diam., bears S15°W, 67 lks. dist., with scribe marks T9S R37E S33 BT visible on open blaze. A pine stump, 22 ins. diam., bears N20°W, 21 lks. dist., no marks visible. At the corner point set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. (SEE DIAGRAM) from which new bearing trees: A ponderosa pine, 9 ins. diam., bears N62 1/2°E, 142 lks. dist., mkd. T9S R37E S27 BT. A ponderosa pine, 7 ins. diam., bears S32°W, 102 lks. dist., mkd. T9S R37E S33 BT. A fir, 8 ins. diam., bears N13°W, 102 lks. dist., mkd. T9S R37E S28 BT. No other suitable trees available within limits.

Description of corner evidence found:

Found 2 1/2" iron post with a 3 1/2" brass cap stamped as shown in diagram. Monument is projecting 10 inches out of the ground and surrounded by a mound of stone. Monumented is solid and in good condition.

- White Fir, 12" dia., healed blaze, bears N15°14'W, 66.52 ft. Established by the BLM (Rec: N13°W, 67.32 ft.)
 - Ponderosa Pine, 16" dia., healed blaze, bears N60°40'E, 91.81 ft. Established by the BLM (Rec: N62 1/2°E, 93.72 ft.)
 - Ponderosa Pine, 14" dia., healed blaze, bears S31°08'W, 67.36 ft. Established by the BLM (Rec: S32°W, 67.32 ft.)
 - Douglas Fir snag, 18" dia., with scribing "T9S R37E" visible on partially healed blaze, bears S13°56'W, 43.74 ft. Established by the Orig. Surveyor (Rec: S15°W, 44.22')
 - Ponderosa Pine stump, 20" dia., with "BT" visible, bears N44°41E, 6.05 ft. Set by Org. Surveyor (Rec: N50°E, 6.60')
- Measurements to existing BT's taken with an Electronic Tacheometer with bearings based on the survey control network.

Description of monument and accessories I established to perpetuate the original location of this corner:

No work is needed on the monument.
From Which:

- A Ponderosa Pine, 10" in dia., bears S85°30'E, 24.8 ft., scribed: T9S R37E S34 BT.
- Nailed a brass washer stamped PLS 848 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) sign above blaze and Land Survey Monument (54-9) sign on back of tree as required. Painted a 6" red band above Bearing Trees sign. Measurements to BT taken with a magnetic compass, declination 20° East, and a nylon clad steel tape. Set steel fence post with Land Survey Monument (54-9) sign 5' north of the monument.

REGISTERED PROFESSIONAL LAND SURVEYOR

This work is performed by:
Douglas M. Ferguson PLS 848
Witnessed by:
D. Mitchell Ferguson & Rick Saul
March 29, 1991
Refer to Baker Co. Survey No. 9-37-181

Office of _____
State of _____
in this office for record on the _____ day of _____, 19____

County of _____
hereby certify that the within instrument was filed
by _____

(COUNTY OFFICIAL)

(DEPUTY)

FILED /-22-92-
BAKER COUNTY SURVEYOR
OFFICE NO. 9-37-181