



(S. 89° 43' W., 80.34)

(S. 89° 46' 40\" E., 2637.77'

(S. 89° 27' W., 79.88)

(S. 88° 47' 37\" E., 2668.49'

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

(S. 89° 27' W., 79.88)

BASIS OF BEARING:
Solar observation and
O.S.H.D., Woodwell base
line bears N. 8° 21' E.

LEGEND

- ⊙ Found monument as described
- Set 5/8" x 30" rebar with plastic cap marked "HANLEY ENGR. PLS 1206"
- () G.L.O. plat data

CORNER POINT LANDS IN
CRACKER CREEK, TWO
BRASS CAP REFERENCE
MONUMENTS ESTABLISHED
BY CO. SURVEYOR IN 1979.
SURVEY NO. 9-37-51

CORNER POINT LANDS IN
MCCULLEY FORK, TWO
BRASS CAP REFERENCE
MONUMENTS ESTABLISHED
BY P.L.S. 1639 IN 1979.
SURVEY NO. 9-37-23

NARRATIVE

Section 29, T. 9 S., R. 37 E., W.M. was surveyed and subdivided by the undersigned in 1971 - 1974, preparatory to marking a corner of Dave A. Simonson property. None of the original quarter corners or their accessories were recovered at that time.

The Sumpter Townsite Syndicate surveyed this section in 1899. The original notes of the STS Survey were furnished by Arthur H. Woodwell, Oregon R.P.E. 1738, a Sumpter resident. Those notes were used to relocate the North quarter corner by retracing the STS traverse calls along the mid-section line between North and South 1/4 corners. I chose to accept the notes bearing of this line N. 01° 27' W., as the most reliable evidence of North quarter corner tie, discounting the STS distance call between the quarter corner and Northeast section corner due to STS notes poor error of closure about 1:1100.

Leland Myers, P.L.S. informed me in early July, 1979 that he believed a burned and rotted stump could possibly be the remains of the original bearing tree for this quarter corner location. Upon investigation by Bill Hanley the marked quarter corner stone was uncovered, identified, and a brass cap monument established in the rock mound on July 5, 1979, by PLS 1639.

The true quarter corner is 2708 feet North and 14.22 feet West of the point previously located under Survey 9-37-5.

Section 29 exterior lines were resurveyed, the resulting traverse of which is shown on this amended map of survey. The East, West and South quarter corner monuments were not field adjusted to this survey, being within acceptable limits.

The previously set 5/8 inch rebars for the North line of the W1/2NE1/4NW1/4 were moved to their proper positions based upon the found and remonumented North quarter corner and Section 29 North line retraverses.

This map amends the No. 9-37-5 map of survey.

**AMENDED
MAP OF SURVEY**

SECTION 29
T. 9 S., R. 37 E., W.M.
SURVEYED NOV. 19, 1993
SCALE 1" = 600'

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James D. Hanley
OREGON
SEPTEMBER 23, 1977
JAMES D. HANLEY
1206

Renewal Date Jan. 1, 1994

HANLEY ENGINEERING
2043 MAIN STREET
BAKER CITY, OREGON

FILED 12-3-93
BAKER COUNTY SURVEYOR
SURVEY NO. 9-37-222