

NOTE: Meridian used this survey is based on the line between sections 29 & 30, T9S R40E W.M. from the section corner north to the 1/4 cor. intervisible.

30
29
2640.51
(80.00ch)
16774
(160th)
30
31
32
N 00° 39' 37" E
1316.04
(80.00ch)
N 00° 39' 37" E
1316.04
31
32
N 00° 39' 37" E
1316.04

Found an iron pin in a mound of stone for 1/4 cor bet. sec's 29 & 30 T9S R40E W.M.

Found an iron pin in a mound of stone for sec. cor. com. to sec's 29, 30 & 31, 32, T9S, R40E W.M.

Found an iron pin placed by a post in a rock jack for W 1/4 cor. bet. sec's 29 & 32, T9S, R40E. The iron pin is 1.98 ft north & 0.6 feet east of proportionate point on line between 1/4 cor. and section corner.

Set iron pin in mound of stone for N 1/4 cor bet. sec's 31 & 32 T9S R40E W.M.

Set iron pin in mound of stone for NW 1/4 cor. of sec. 32 T9S, R32E W.M.

Set iron pin in mound of stone in fence line for NE 1/4 cor. sec. 32 T9S R40E W.M.

Found a stone marked 1/4 on the east face in a mound of stone for 1/4 cor. bet 31 & 32 T9S R40E

$\Delta = 37^{\circ} 40' R$
 $D = 13^{\circ} 00'$
 $T = 130.34$
 $E = 21.94$
 $Lc = 289.77$

Proposed Parcel
Contains 39.972 acres
Less Road 0.941 acres
Total Remaining 39.031 acres

SURVEY OF THE NE 1/4 NW 1/4 SEC. 32
T9S R40E W.M.
Scale 1" = 200' March 1970

NOTE: Full subdivision of section 32 has been made 10-23-72. There for all adjustments shown here have been made in field as to that survey.

FILED March 28, 1973
BAKER COUNTY SURVEYOR
SURVEY NO. 9-40-16

REGISTERED
OREGON
LAND SURVEYOR
JAMES H. HAMBLETON
4-20-70
JULY 10, 1964
JAMES H. HAMBLETON
645

