

S. 88° 40' 22" W, 1301.38

N. 01° 22' 34" W, 1320.34

Meridian based on map of
CITY SURVEY OF 1970

1326.28

651.61

N. 88° 48' 10" E.

651.61

353.82
(362.5 ±)

363.80
(363.8)

661.51
362.5 (361)

N. 88° 56' E. 353.97

N. 01° 28' 40" W.
662.31

(299)
N. 01° 27' 18" W. 299.0

299.0

200

100

200

(299)

354.07

Deed 71-13-033

100

30

30

30

30

30

30

30

30

30

30

30

30

30

30

30

30

30

30

30

30

30

30

O.S.H.D. R/W.

(366.7 ±)

364.45

40

50

50

50

50

50

50

50

50

50

50

50

E 107+39.02 P.S.

S. 01° 32' E, 663.14

E 109+39.02 P.S.C.

1/16 Cor.

End. P.K. Nail

Found 1/4 cor. monument in 180 road fill, East side of West-bound.

Found city mon. CENTER OF SEC. 16

T. 9 S., R. 40 E., W.M.

SEE "CITY SURVEY OF 1970" for the subdivision of Sec. 16, T. 9 S., R. 40 E., W.M. Distances shown in parenthesis are those in deed records. See attached narrative.

FILED June 9, 1977 BAKER COUNTY SURVEYOR SURVEY NO. 9-40-97 BC

MAP OF SURVEY FOR JACK WENDT May & June, 1977 Scale: 1"=100'

REGISTERED PROFESSIONAL LAND SURVEYOR James D. Hanley OREGON SEPTEMBER 23, 1917 JAMES D. HANLEY 1206

• Set 1/2" rebar on May 25, 1978, and added to this map. J.D.H.