Found, 5/8" rebar NW Cor., NW¼ NE¼

N. 88°24'39"E., 1297.75'

Found, ½" rebar NE¼ Cor., NW¼ NE¼

H STREET

G STREET

F STREET

E STREET

D STREET

Meridian based on City Survey, 1970.

N. 01°22'34"W., 1320.32'

Platted EAST FOURTEENTH

N. 01°32'00"W., 1326.27'

NOW BIRCH

TENTH EAST

ELEVENTH EAST

TWELFTH EAST

THIRTEENTH EAST

Platted

250.08'

40'

30'

N. 88°36'26"E., 780.41'

N. 88°40'22"E., 1241.38'

N. 88°38'01"E., 100.62'

N. 01°25'25"W., 120.20'

N. 01°31'04"W., 120.56'

N. 01°32'00"W., 120.60'

N. 01°25'25"W., 115.30'

N. 01°31'04"W., 115.54'

N. 01°32'00"W., 115.90'

200.14'

200.28'

100.07'

100.14'

60'

700'

100'

75'

90'

100.78'

100.10'

100.07'

115.37'

115.42'

115.48'

115.61'

115.68'

115.73'

115.78'

115.83'

• Indicates set ½" rebar unless otherwise noted

Found, ½" rebar SW Cor., NW¼ NE¼

5/8" rebar

Found, ½" rebar SE Cor., NW¼ NE¼

MAP OF SURVEY

IN THE NW¼ NE¼ SECTION 16, T. 9S., R. 40E., W.M.

(FORMERLY FAULL'S ADD'N, BAKER, ORE.)

Surveyed June 30 & July 29, 1977 Scale 1"=100'

for John Linscott

REGISTERED PROFESSIONAL ENGINEER 2808 James D. Hanley OREGON May 1, 1948 JAMES D. HANLEY

FILED Aug. 8, 1977

BAKER COUNTY SURVEYOR

SURVEY NO. 9-40-104 BC