

NE 1/4 SEC. 20, NW 1/4 SEC. 21, T 9 S, R 40 E, W. M.

LEGEND

- (\*) M.E. PLACE'S ADDITION
- ( ) OSHD DRG. 6B-2-21 OR AS NOTED
- [ ] OSHD DRG. 3B-22-23
- ▲ SET NETWORK POINT
- △ FOUND MONUMENT USED AS NETWORK POINT
- FOUND MONUMENT AS NOTED
- RETRACED CENTERLINE
- R/W OR PROPRTY BOUNDARY

NOTES

- ① PT. 1008: FND. 16mm (5/8") IRON ROD IN MONUMENT BOX, ACCEPT FOR INTERSECTION OF AUBURN ST. AND DEWEY AVENUE, CS 9-40-136 BC, 9-40-293  
N 126619.386  
E 2711755.962
- ② PT. 1015: FND. 25mm (1") DIA. BOLT IN MONUMENT BOX, ACCEPT FOR INTERSECTION OF PLACE ST. AND DEWEY AVE., HANLEY SURVEY OF MAY 26, 1954;  
CS 9-40-186, 9-40-187  
N 126519.439  
E 2711732.195
- ③ PT. 12: 12mm (1/2") FND. IRON ROD IN MONUMENT BOX, ACCEPT AS POINT FOR ELM ST., CS 9-40-99 BC,  
CS 9-40-357  
N 126425.681  
E 2711991.953
- ④ PT. 1014: FND. 12mm (1/2") IRON ROD UNDER ASPHALT DESCRIBED AS IRON PIPE BY CS 9-40-187  
N 126461.318  
E 2711691.542
- ⑤ BAKER CITY VACATION ORDINANCE 1077  
A - (S15°59'W 75.63') FROM SECTION CORNER (THENCE S00°39'E 120.24') (THENCE S25°07'W 51.48')  
B - (THENCE N7°55'E 163.45')

