

T.9S., R.44E.
T.9S., R.45E.

N. 02° 37' 25" W, 1306.99' bet. fence cors.

Accepted fence corner for
1/4 section corner = NW cor.
SW 1/4 Section 18.

N. 84° 34' 35" E, 2460.15' bet. fence cors.

SOUTH, 68.74' →

N. 80° 20' 30" E.

S. 78° 45' 30" E, 175.44'

N. 87° 51' 50" E, 171.74'
N. 75° 03' 15" E, 137.5' ±

NORTH RIGHT-OF-WAY LINE
O.S.H.D. BAKER HOMESTEAD HWY.
N. 30° 52' E.

O.S.H.D. BAKER - HOMESTEAD HWY.
N. 64° 10' E.

9° C.R.
T_Δ = 28° 30' 35"
T_S = 237.67
S = 6° 45'
Q = 6.0
PT 1839 + 31.99
PS 1834 + 64.10

380' SP
S = 14° 26' 4"
Q = 2.0
PS 1840 + 07.01

7° 36' C.R.
T_Δ = 35° 18' 00"
T_S = 417.44

380' SP
S = 14° 26' 4"
Q = 2.0

PT 1848 + 25.17
PT 1846 + 90.15

300' SP
S = 6°
Q = 1 1/3
PS 1848 + 46.48

4° C.R.
T_Δ = 16° 10' 30"
T_S = 353.86'

300' SP
S = 6°
Q = 1 1/3

PT 1856 + 50.86

1858 + 75.80
PS 50

WZG
Bearings based on OSHD Map
No. 7B-34-15 - The tangent bet.
ween PT 1905 + 25.96 and
PS 1913 + 65.67 bears N. 70° 56' 50" E.

MAP OF SURVEY FOR LORIN STANCIU SHOWING PARCEL AS FENCED IN THE SW 1/4, SEC. 18, T.9S., R.45E., W.M.

Surveyed Nov. 30 & Dec. 4, 1979

Scale 1" = 200'

FILED Jan. 4, 1980
BAKER COUNTY SURVEYOR
SURVEY NO. 9-45-20

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William L. Hanley

OREGON
JULY 14, 1978
WILLIAM L. HANLEY
1639