

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

William R. Gradon, U.S. Deputy Surveyor
July 1, 1882

39.80 Set a post 3 ft. long, 3 ins. square, 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N. face, from which:

A pine, 24 ins. diam., bears N.35°E., 74 lks. dist., mkd. $\frac{1}{4}$ SBT.
A pine, 20 ins. diam., bears S.40°W., 58 lks. dist., mkd. $\frac{1}{4}$ SBT.

DIAGRAM
T 10 S R 37 E

S 10
 $\frac{1}{4}$ -----
S 15

PLS 699
1994

Description of corner evidence found:

Found a 3" aluminum capped pipe, set flush to the ground from which:

A stump, bears S.39°17'W., 39.2', with FS signs no marks visible.
A pine, 12" in diam., bears S.72°44'W., 45.2', scribed " $\frac{1}{4}$ S15BT".
A pine, 6" in diam., bears N.22°54'W., 20.4', scribed " $\frac{1}{4}$ S10BT".

Description of monument and accessories I established to perpetuate the original location of this corner:

REGISTERED
PROFESSIONAL
LAND SURVEYOR

R. David Schurian 7-15-96

OREGON
JUNE 18, 1976
R. DAVID SCHURIAN
1060

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____

(COUNTY OFFICIAL)

(DEPUTY)

J-15

FILED 7-15-96

BAKER COUNTY SURVEYOR

SURVEY NO. 10-37-96