

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Not previously set.

DIAGRAM

1 S 8
W- ----
16 S 17

RLS 1060
1995

Description of corner evidence found:

Corner is being set by this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the point, determined by the procedures in the MANUAL OF INSTRUCTION FOR THE SURVEY OF PUBLIC LANDS, set a USFS 3¼" aluminum capped monument 16" in the ground, with a small mound of stone to cap, form which:

A fir, 7" in diam., bears S.55°40'E., 37.6 ft., double blazed and scribed "W1/16S17BT" with nail and brass washer "RLS 1060", on face of blaze.

A pine, 10" in diam., bears N.26°E., 64.7 ft., double blazed and scribed "W1/16S8BT" with nail and brass washer "RLS 1060", on face of blaze.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

R. David Schurian 7-15-96

OREGON
JUNE 18, 1976
R. DAVID SCHURIAN
1060

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____

(COUNTY OFFICIAL)

(DEPUTY)

J-6

FILED 7-15-96

BAKER COUNTY SURVEYOR

SURVEY NO. 10-37-93