

as follow:

In 1971 The Bureau of Land managment, monumented the corners
The corner of sections 4,5,8, and 9 determined at record bearing and
distance from the remains of the original bearing trees:

A root hole, bears $N40^{\circ}E$, 130 lks dist. with a down Pine alongside, 50" dia.
with illegible scribe marks visible on open blaze.

A Root hole, bears $S70^{\circ}W$, 28 lks dist. with a down Pine alongside, 36" dia.
with scribe marks T10S R37E S8 BT. visible on open blaze.

A Pine 40" dia. bears $N5^{\circ}W$, 64 lks dist. with scribed marks T10S R37E S5 BT.
visible on partially open blaze.

At corner point.

Set an iron post, 28" long $2\frac{1}{2}$ " dia. 24" in the ground, with brass cap mkd.

T10S R37E
S5 | S4
S8 | S9
1971

From which new bearing trees.

A Ponderosa Pine 11" dia. bears $N68^{\circ}E$, 60 lks. dist. mkd. T10S R37E S4 BT.

A " " 8" dia. bears $S58^{\circ}E$, 76 lks dist. mkd. T10S R37E S9 BT.

A " " 10" dia. bears $S65^{\circ}W$, 4 lks dist. mkd. T10S R37E S8 BT.

A " " 10" dia. bears $N20^{\circ}W$, 121 lks dist. mkd. T10S R37E S5 BT.

Bury a granite stone $15 \times 9 \times 7$ " with an X chissled on W. face and deposit a glass
bottle alongside iron post.