

22 23
27 26

23 24
26 25

The South line SW $\frac{1}{4}$ bears
S. 89° 51' W. as recorded
in original GLO survey.

LEGEND

- ⊙ SET 2 $\frac{1}{2}$ " BRASS CAP ON 1" I.P.
- () RECORD OF ORIGINAL GLO SURVEY

NOTE: FOR MONUMENTATION
DETAILS SEE CERTIFIED RECORD
OF LAND CORNER MONUMEN-
TATION SHEETS FILED SEPARATELY.

(NORTH, 80.0)

1311.64' N. 0° 44' 40" W. 1311.64'

26

S $\frac{1}{2}$ SW $\frac{1}{4}$

27 26
34 35

S. 89° 51' 00" W. 2560.85'

(S. 89° 51' W. 80.14)

26 25
35 36

NARRATIVE:

The NW corner of the S $\frac{1}{2}$ SW $\frac{1}{4}$, Section 26, was set midway between the found NW corner and the SW corner of the SW $\frac{1}{4}$, Section 26, in full accordance with prescribed survey methods.

MAP OF SURVEY

IN THE SW $\frac{1}{4}$ OF SECTION 26, T.10S., R.41E., W.M.

Surveyed Jan. 15 & 16, 1981

Scale 1"=800'

For Sid Johnson

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James D. Hanley

OREGON
SEPTEMBER 23, 1977
JAMES D. HANLEY
1206

FILED Jan. 19, 1981

BAKER COUNTY SURVEYOR

SURVEY NO. 10-41-5