History of original corner establishment:

N/A

DIAGRAM

T11S R37E N 1/16 S23|S24

Description of corner evidence found:

N/A

Description of monument and accessories I established to perpetuate the original location of this corner:

T11S R37E N 1/16 S23/S24 1995 LS 896

Set: $2\frac{1}{2}$ "30" alum. pipe with a $2\frac{1}{2}$ " alum. cap 26" in ground next to Pine stump. Stamped:

Marked:

8" Ponderosa Pine N58W--9.2' Scribed N 1/16 S23 BT.
28" Ponderosa Pine N50E--11.8' Scribed N 1/16 S24 BT.
Nailed 54-9 and 5-3 signs to BT's, painted bands and blazes red and nailed a 1" brass disk stamped PLS 896 flush between the B and T.
Set guard posts North and West with 54-2 signs, one with 54-9 sign.

Bearings are true by instrument tie.

FERRING LE/1/195

Office of	County of
State of, / hereby co	ertify that the within instrument was filed in this office
for record on the day of	, 19
***************************************	by
(COUNTY OFFICIAL)	(DEPUTY)

Form R6-7100-57 (9/71)

FILED FEB.4, 1998
BAKER COUNTY SURVEYOR
SURVEY NO. 11-37-84

*GPO-591-971, 1988