

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of Original Corner Establishment:

The original cadastral survey was performed during September of 1881 by George Henderson, Deputy Surveyor, under contract number 409. He set a stone 14" x 8" x 4" for corner to sections 27, 28, 33 and 34 marked T 12 S S 28 on NW, S 27 on NE, S 33 R 41 E on SW, and S 34 on SE faces respectively; a raised mound of stones around the stone.

A retracement survey was performed by Lincoln E. Wilkes, Cadastral Surveyor, dated June 4, 1917. At this corner, he said he found a sandstone 12" x 8" x 4", loosely set in a mound and dimly marked R 41 E S 33 on SW face. To perpetuate this corner, at the exact corner point, he set a water worn quartzite stone, 16" x 14" x 10", 12 inches in the ground for corner of sections 27, 28, 33 and 34 marked with one notch on South and three notches on East edges and raised a mound of stone 2 feet at base 1 1/2 feet high West of corner.

Description of Corner Evidence Found:

At this section corner location I found a water worn quartzite stone, 16" x 14" x 10" loosely set about 6 inches in the ground with a large mound of stone directly to the West of the corner point. The stone is clearly marked, as shown in the accompanying photo, with one notch on the south and three notches on the east faces, agreeing with Wilkes' GLO notes of the survey of 1917.



Found cornerstone and mound in place as described in GLO notes.

Description of Monument and Accessories I Established to Perpetuate the Original Location of Corner:

At the exact location of the cornerstone, I placed a 2 1/2 inch brass monument affixed to the top of a 1" x 30" flared galvanized pipe. The brass cap is about 6 inches above the surface of the ground and stamped as shown in the accompanying photo. I placed the original stone upside down and buried along the west face of the monument, with a raised mound of stones around the monument, flush with the top of the cap. I did not disturb the mound of stone found to the west of the monument. I left it in its original position. From which I set four new bearing trees described as follows:

A Juniper 8 inches in diameter, bears N 77 30 E, 65.80 feet horizontal distance, blazed and scribed T 12 S, R 41 E, S 27 BT. I placed a brass washer stamped ORLS 645 at the base of the blaze.

A Juniper 7 inches in diameter, bears N 72 30 W, 65.10 feet horizontal distance, blazed and scribed T 12 S, R 41 E, S 28 BT. I placed a brass washer stamped ORLS 645 at the base of the blaze.

A Juniper 26 inches in diameter, bears S 64 15 W, 78.50 feet horizontal distance, blazed and scribed T 12 S, R 41 E, S 33 BT. I placed a brass washer stamped ORLS 645 at the base of the blaze.

A Juniper 12 inches in diameter, bears S 50 15 E, 81.70 feet horizontal distance, blazed and scribed T 12 S, R 41 E, S 34 BT. I placed a brass washer stamped ORLS 645 at the base of the blaze.



One notch on South and three notches on East faces of water worn quartzite stone, 16" x 14" x 10".



Brass cap as stamped.

This section corner's geographic position.
44 29 15.14116 N, 117 41 27.16085 W
NAD 83.

I, James H. Hambleton certify that this corner was properly reestablished as witnessed by John Eggers on June 9, 2011.

FILED June 28, 2011
BAKER COUNTY SURVEYOR
SURVEY NO. 12-41-14

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

Renews June 30, 2012

12-41-14